

Rocker Switches



SERIES	FEATURE	MAX RATING (Resistive @ 28VDC)	SEAL RATING	APPROVALS	MOUNTING (Panel Opening)	CIRCUITRY
K1	Sealed, Illuminated Single Pole	16A	IP68S & IP69K	UL (E61705), (UL1500), Ignition Protected, RoHS Compliant	1.115" x 0.515"	SPST, SPDT
K1S	Sealed, ON-ON-ON, Single or Double Pole	10mA @ 5VDC	IP68S	RoHS Compliant (based on configuration)	1.077" x 0.485"	SPTT, DPST
K2	Sealed, Illuminated Double Pole	16A	IP68S & IP69K	UL (E61705), (UL1500), Ignition Protected, RoHS Compliant	1.115" x 0.900"	SPST, SPDT DPST, DPDT
K3	Sealed, Illuminated	20A	IP68S & IP69K	RoHS Compliant	1.750" x 0.915"	SPST, SPDT DPST, DPDT, SPTT
K3P	Panel Plug Indicators	20mA	IP68S	RoHS Compliant	1.750" x 0.915"	Lighting: Ind A, Ind C, Ind A & C
K4	Snap-in Toggle, Sealed, Illuminated	16A	IP68S & IP69K	RoHS Compliant	1.115" x 0.900"	SPST, SPDT DPST, DPDT
K5	Sealed, Illuminated	20A	IP68S & IP69K	RoHS Compliant	1.475" x 0.875"	SPST, DPDT SPDT, DPDT, SPTT
U2	Sealed, High Cycle Life	10A (10mA @ 5VDC logic level)	IP64 or IP68S	RoHS Compliant	1.125" X 0.690"	SPST